

ROAD COMMISSION FOR OAKLAND COUNTY

SPECIAL PROVISION  
FOR  
**AGGREGATE APPROACH AND SHOULDER**

RCOC/DESIGN:CJ/JO

PAGE 1 OF 1

RCOC20SP307A

ORG:10-27-20

REV:10-29-24

**a. Description**

This work shall be done in accordance with section 307, Aggregate Shoulders and Approaches, of the *Michigan Department of Transportation (MDOT) 2020 Standard Specifications for Construction*, except as provided herein.

**b. Materials**

Use material meeting grading and physical requirements for Michigan Class 21AA dense- graded aggregate as specified in section 902, Aggregates, of the *MDOT 2020 Standard Specifications for Construction*. The material shall be produced entirely from natural aggregates. The use of crushed concrete aggregate is not allowed.

**c. Construction**

The density requirement for this material is to compact not less than 95 percent of the maximum unit weight at moisture content not greater than optimum when placed equal to or greater than 6 inches in depth. When the material is placed less than six (6) inches in depth, compact by mechanical means as directed by the Engineer.

**d. Measurement and Payment**

The completed work, as described, will be measured and paid for at the contract unit price with any adjustments covered in this special provision, using the following pay items:

<b>Pay Item</b>	<b>Pay Unit</b>
Approach, 21AA, _ inch.....	Square Yard
Approach, 21AA.....	Ton
Shld, 21AA, _ inch.....	Square Yard
Shld, 21AA.....	Ton

These pay items will be paid for as specified in Aggregate Shoulder and Approaches, section 307.04.B. Payment includes equipment, labor, and materials to complete these items.