

ROAD COMMISSION FOR OAKLAND COUNTY

S.A.D. SPECIAL PROVISION
FOR
DITCHING, SAD

RCOC/SAD:RS/YE

Page 1 of 1

20SAD205A
ORG: 03-09-21

a. Description.

This work shall consist of all earth work necessary to construct new ditches, and/or re-grade, and/or clean out existing ditches as shown on the plans and details or as directed by the Engineer. This work shall be done in accordance with the requirements of Section 205 of the *2020 Michigan Department of Transportation Standard Specifications for Construction*, and as indicated herein.

b. Materials.

All work shall be in accordance with the contract documents.

c. Construction.

Tolerance for Trimming and Finished Earth Grade.

The tops of back slopes, bottoms of fill slopes and all other angles in the lines of the ditch cross section shall be rounded to form vertical curves as shown on the plans or as required by the engineer. All transitions in length of vertical curves shall be gradual and shall present a uniform and attractive appearance. When ditches are constructed in peat, vertical curves may be omitted at the discretion of the engineer.

d. Measurement and Payment.

The completed work for Ditching, SAD including all labor, equipment and material necessary to complete this work as specified above, shall be measured and paid for at the contract unit price for the following item:

Pay Item	Pay Unit
Ditching, SAD.....	Foot

Ditching, SAD shall be measured along the centerline of the ditch. Payment for this item shall be payment in full for all costs associated with constructing the ditch to grade including excavation and embankment, as well as off-site disposal of unsuitable or excess material. Restoration of green belt in and/or adjacent to ditches will be measured and paid for separately as provided on plans.