

ROAD COMMISSION FOR OAKLAND COUNTY

SPECIAL PROVISION
FOR
DITCHING, RCOC

RCOC/DESIGN:KS/JO

PAGE 1 OF 1

RCOC20SP205A
ORG:02-14-21

a. Description

This work shall be done in accordance with section 205 of the *Michigan Department of Transportation (MDOT) 2020 Standard Specifications for Construction*, except as herein provided.

Complete all earth excavation and embankment required to reshape and/or move a ditch to restore or establish positive drainage. The Engineer will provide the grade, shape, and location of the ditch. Dispose of excess material according to subsection 205.03.P of the *MDOT 2020 Standard Specifications for Construction*.

b. Materials

If additional embankment is required, use Sound Earth or other material as approved by the Engineer.

c. Construction

Ditching, RCOC may include, but is not limited to, the following work:

1. Reshape and move existing ditch.
2. Remove cattails, brush and miscellaneous debris.
3. Remove trees less than 3 inches in diameter.
4. Flatten fill slopes around culvert extensions.
5. Blend ditch profile to match existing ditch.
6. Removing soils/spoils from the project site.

Excavated earth may be used to fill old ditches and/or flatten fill slopes at culvert extensions.

d. Measurement and Payment

The completed work, as described, will be measured and paid for at the contract unit price using the following pay item:

Pay Item	Pay Unit
Ditching, RCOC.....	Foot

Ditching, RCOC will be measured along the ditch centerline and will include all labor, equipment and materials required to complete the work as described.

Additional embankment and turf establishment items, if required, will be measured and paid for separately.