

ROAD COMMISSION FOR OAKLAND COUNTY

SPECIAL PROVISION
FOR
CURB HEAD REMOVAL

RCOC/DESIGN:KS/JO

PAGE 1 OF 1

RCOC20SP204A
ORG:02-14-21

a. Description

This work shall be done in accordance with sections 204 and 802 of the *Michigan Department of Transportation 2020 Standard Specifications for Construction*, except as herein provided.

This work shall consist of removing the head of existing curb and gutter sections as shown on the plans and/or directed by the Engineer.

b. Materials

None specified.

c. Construction

The Contractor shall remove the existing curb head flush to the existing gutter pan by a method approved by the Engineer. In areas where the existing driveway opening conforms to MDOT Concrete Driveway Opening, Detail M, the contractor shall remove the curb head to the point where the driveway return meets the mainline curb and gutter.

Provide a final surface texture that is reasonably smooth and free of gouges, holes or large depressions. The Contractor shall prevent damage to the adjacent pavements. Where material is removed below the depth specified due to poor removal practice, remove and repair the curb and gutter area in accordance with sections 204 and 802 as directed by the Engineer. All costs associated with this corrective work will be borne by the Contractor. Repair all damage to adjacent surfaces as directed by the Engineer. All costs associated with this corrective work will be borne by the Contractor.

d. Measurement and Payment

The completed work, as described, will be measured and paid for at the contract unit price using the following pay item:

Pay Item	Pay Unit
Curb Head, Rem.....	Foot

Curb Head, Rem includes all equipment and labor required for removing, loading, hauling, disposal of the material, and any repairs, if required.