

ROAD COMMISSION FOR OAKLAND COUNTY

SPECIAL PROVISION
FOR
AGGREGATE BASE COURSE

RCOC/DESIGN:CJ/JO

PAGE 1 OF 1

RCOC20SP302A
ORG:10-27-20

a. Description

This work shall be done in accordance with section 302 of the *Michigan Department of Transportation (MDOT) 2020 Standard Specifications for Construction*, except as herein provided.

b. Materials

The material shall meet the requirements specified in Tables 902-1 and 902-2 of the *MDOT 2020 Standard Specifications for Construction*.

RCOC will sample the aggregates at the jobsite at any time prior to rolling and compacting, for gradation and other specification compliance testing.

Materials shall be produced entirely by crushing rock, boulders, cobbles or slag. Only fines produced by the crushing process shall be permissible; no plastic fines shall be added. Crushed concrete will not be allowed.

The Contractor will be solely responsible for degradation and segregation during shipment, placement and compaction of the material.

c. Construction

Do not use Sodium Chloride to aid in placing and compacting aggregate base.

d. Measurement and Payment

The completed work, as described, will be measured and paid for at the contract unit price using the following pay items:

Pay Item	Pay Unit
Aggregate Base, __ inch, 21AA, RCOC.....	Square Yard
Aggregate Base, LM, 21AA, RCOC.....	Cubic Yard
Aggregate Base, 21AA, RCOC.....	Ton

Payment includes equipment, labor, and materials to complete the item of work.